

CORE

TECHNOLOGY:	TRUE ON LINE Double Conversion
CLASSIFICATION:	VFI-SS-111 (EN 62040-3)
POWER RANGE:	1 - 10 kVA
No. OF PHASES:	1:1



■ APPLICATIONS

- Servers
- Working stations
- Lighting
- Laboratory equipment
- Security systems
- Automation and control systems

■ SPECIFICATION

Technology True On-Line Double Conversion Technology provides perfect output voltage parameters, regardless of the input voltage and the load.

Automatic bypass provides continuous load supply in critical conditions, such as overheating or inverter failure.

Communication:

USB, RS232 for UPS and load supervision and control.

TVSS to protect tele information equipment.

SNMP slot allows connect SNMP card to manage UPS throw network or AS400 card with potential free contactors.

LCD control panel displays UPS and power parameters as well as hundreds of useful information.

Small dimensions only 2U control panel displays UPS and power parameters as well as hundreds of useful information.

High efficiency up to 95% in online mode to minimizes energy consumption and reduces heat emissions, which makes cooling of rooms cheaper.

ECO-Mode allows 990% efficiency and additional energy savings.

CVCF Frequency converter mode allows UPS to operate in the 50 Hz or 60 Hz to supply non-standard receivers.

Automatic diagnostics guarantee full device performance, control of components and operating parameters without user intervention.

The high value of input power factor restricts the current value of the device from professional network.

Wide input voltage range for normal mode ensures that batteries are used only if necessary – in fact, only when the input voltage is completely lost.

Rechargeable battery charger for 6 and 10kVA units gives ability to connect high capacity batteries for long autonomy.

The ability to extend the backup time by adding battery modules allows you to precisely adjust the required autonomy time.

The high output power factor PF=1 guarantees up to 30% more active power compared to other power supplies in this class.

Wide input frequency range for normal mode makes possible to freely use the power supply in a mixed network of city-generator.

Auto restart guarantees maintenance-free operation in case of long power failure.

Cold start provides possibility to launch UPS without main voltage.

Advanced battery management guarantees optimum battery charging and usage. The 3-stage charging process extends their service life up to 50% and reduces operating costs.

Excellent voltage quality achieved by using the IGBT (3L) inverter and high frequency PWM modulation ensures that the voltage is delivered in extremely stable parameters, regardless of power interference and the type of power supply.

Overload resistance is reliable power supply with transient states and high fault tolerance.

Advanced software gives the user complete control over the device and the power receivers.

REPO connector provides the ability to remotely switch off the power supply in the case of fire.

Programmable output sockets allows you to manage the presence of output voltage during battery operation.

Parallel operation for 6 and 10kVA units provides maximum reliability for critical load.

CORE

Model	Core 1K	Core 2K	Core 3K	Core 6K	Core 10K
Power	1000 VA / 900 W	2000 VA/ 1800 W	3000 VA / 2700 W	6000 VA / 6000 W	10 kVA / 10kW
No. Of phases IN : OUT	1:1				
Input					
Voltage	208 / 220 / 230 / 240 VAC				
Voltage range	-30% ÷ +30% @ 100% ≥ obc. ≥ 80% -40% ÷ +30% @ 80% ≥ obc. ≥ 70% -48% ÷ +30% @ 70% ≥ obc. ≥ 60% -52% ÷ +30% @ 60% ≥ obc. ≥ 0%				
Frequency	50 / 60 Hz				
Frequency range	-20% ÷ +20%				
THDi	<3%				
Input power factor	≥0,99				
Output					
Voltage	208 / 220 / 230 / 240 VAC				
Output power factor	0,9			1,0	
Voltage regulation static/dynamic	±1% / ±3%				
Frequency	50 / 60 Hz ± 0,05 Hz				
Overload capacity inverter	110% - no limit, 130% - 5 min., 140% - 30 sec., >140% - 1,5 sec.			110% - 10 min., 130% - 1 min., > 130% - 1 sec.	
Efficiency On-Line mode	>92%			>95%	
Efficiency Eco mode	99%				
Controlled socket groups – with programmable power off	1 x 4 psc.			n/a	
Type and number of sockets	IEC320-C13 x 8	IEC320-C13 x 8	IEC320-C13 x 8 IEC320-C19 x 1	n/a	
Terminal board	n/a (Plug&Play)			yes	
Creast factor	3:1				
Batteries					
Backup time (min.)	100 % load	8 / 32	8 / 32	4 / 20	- / 9
	75 % load	12 / 43	12 / 43	7 / 28	- / 13
	50 % load	20 / 73	20 / 73	12 / 42	- / 21
Amount of internal batteries	3 x 7/9 Ah	6 x 7/9 Ah	6 x 7/9 Ah	-	
Cold start	Yes				
Connector for external batteries	Yes				
Charging time	4 hours up to 90% of capacity (configurable)				
Weight and dimensions					
Dimensions and weight of UPS (W x D x H)	438 x 410 x 88 (2U)	438 x 630 x 88 (2U)		438 x 600 x 88 (2U)	
	14,2 kg	26,9 kg	27,4 kg	17,0 kg	20,0 kg
Dimensions and weight of battery module (W x D x H)	438 x 410 x 88 (2U)	438 x 630 x 88 (2U)		438 x 600 x 133 (3U)	
	21,3 kg	40,8 kg		63 kg	
Communications					
Working indicator	LCD + indicators LED, alarm sound alarm				
Communications	Standard: USB, RS232, TVSS, Smart slot, REPO Options: Dry Contact, SNMP card,				
Environmental					
Noise level	<45 dB			<50 dB	
Operating temperature for UPS	0°C ÷ 40°C				
Recommended operating temperature for UPS	15°C ÷ 25°C				
Storage temperature	-25°C ÷ 55°C				
Humidity	0 ÷ 95% (without condensing)				
Certification					
Standards	EN 62040-2:2005, EN 62040-2:2006				
Safety	IEC62040-1-1, CE, 62040-3 :2001				
Options					
- SNMP cards	- Drycontact (AS-400)				
- Environmental sensor (EMD)	- Additional battery module				
- Maintenance bypass	- Rail kits 19"				
- EPO					